

**February 2008 VERONA AGRICULTURAL SHOW**  
**FARESIN HANDLERS PRESENTS TELEHANDLERS LS WITH ENGINE 94 kw (130 HP).**

*Breganze, February 2008* – Available, as an optional extra, in the 7 m to 17 m machine range the new ENGINE 130 HP.

The engine is an Iveco turbo intercooler with STEP 3 type approval in compliance with European directives.

The engine is installed on the side of the structure with the new direct drive configuration for cooling (front engine fan).

With this new type of arrangement the LOAD SENSING SYSTEM can be applied as an optional extra.

LS: this system permits working with a LARGER OIL CAPACITY 120l (standard 94l) and GREATER PRESSURE 270 bar (standard 250 bar).

The LS system includes a variable capacity piston pump, a proportional distributor and 2 different types of proportional joysticks.

The two proportional joysticks can have 1 thumbwheel control for boom extension and a push button for the head ancillary equipment or 2 thumbwheels.

The thumbwheels on the joystick are more ergonomic and provide MORE MOVEMENT SENSITIVITY and consequently also more PRECISION.

The LS system with proportional distributor and piston pump permits using several movements at the same time by choking the flow of hydraulic oil as the capacity changes and adapting it automatically to the hydraulic equipment requirements activated even at low engine rpm.

STAND C16 PAV 8

FARESIN AGRI DIVISION SPA & FARESIN HANDLERS SPA

Via dell'Artigianato, 36 - 36042 Breganze ( VI)

Tel. +39 0445 800300

e-mail: [silviafaresin@faresin.com](mailto:silviafaresin@faresin.com)